

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : High Gloss black - 400ml
Product code : TSP 1010

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial uses: Uses of substances as such or in preparations* at industrial sites
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Consumer uses: Private households (= general public = consumers)
Use of the substance/mixture : Non industrial spraying
Industrial spraying

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Importer

Paint Smart Group NZ
6 Killarney Lane
Hamilton
T +64 7 847 0933 - F +64 7 847 0932
www.paintsmart.co.nz

Supplier

Chemicar Europe
Baarbeek 2
2070 Zwijndrecht, Belgium
T +32 3 234 87 80
www.finixa.com

1.4. Emergency telephone number

Emergency number : Poisons Information Centre New Zealand
0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Repeated exposure, Category 1 H372
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

HSR002517 – Flammable, toxic

Adverse physicochemical, human health and environmental effects

No additional information available

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates (2-25%)
Acetone
xylene (mix)
butanone

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H304 - May be fatal if swallowed and enters airways.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe spray.
P264 - Wash hands thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTRE or doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains (cobalt bis(2-ethylhexanoate)). May produce an allergic reaction.

Scandinavian countries regulation

Denmark

MAL code

: 5-6

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0	10 - 25	Flam. Gas 1, H220 Press. Gas
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5	10 - 25	Flam. Gas 1, H220 Press. Gas

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

butanone; ethyl methyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates (2-25%)	(EC-No.) 919-446-0	10 - 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0	1 - 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	0.1 - 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
cobalt bis(2-ethylhexanoate)	(CAS-No.) 136-52-7 (EC Index-No.) 205-250-6	0.1 - 1	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4	0.1 - 0.25	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : No irritant effect.
- First-aid measures after eye contact : Rinse opened eye for several minutes under running water. Then consult doctor. Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Seek urgent medical help. Obtain medical assistance.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water fog. extinguishing powder. carbon dioxide (CO2). Alcohol resistant foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Protection during firefighting : Approved respirator.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Wear suitable protective clothing. Evacuate area.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Other information : Ensure there is adequate ventilation. Do not flush with water.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Handle and open container with care. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Store in dry, cool, well-ventilated area. Protect from heat and direct sunlight. Container should not be closed gas-tight.

Special rules on packaging : Container should not be closed gas-tight. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)		
Belgium	Local name	Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4) # Alifatische koolwaterstoffen in gas-vorm : Alkanen (C1-C4)
Belgium	Limit value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
acetone; propan-2-one; propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m³)	1210 mg/m³
EU	IOELV TWA (ppm)	500 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Acétone # Aceton
Belgium	Limit value (mg/m³)	1210 mg/m³
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m³)	2420 mg/m³
Belgium	Short time value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
propane (74-98-6)		
Belgium	Local name	Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4) # Alifatische koolwaterstoffen in gas-vorm : Alkanen (C1-C4)
Belgium	Limit value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
Xylene (mix)		
WEL	Short-term value	441 mg/m³, 100 ppm
	Long-term value	220 mg/m³, 50 ppm
	Sk; BMGV	
Ethylbenzene (100-41-4)		
WEL	Short-term value	552 mg/m³, 125 ppm
	Long-term value	441 mg/m³, 100 ppm
	Sk	
cobalt bis(2-ethylhexanoate) (136-52-7)		
WEL	Long-term value: 0.1 mg/m³	
	as Co; Carc, Sen	
DNELs		
acetone; propan-2-one; propanone (67-64-1)		
Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propane (74-98-6)		
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	2,420 mg/m3 (Worker)
	DNEL Long term-systemic	200 mg/m3 (Consumer)
		1,210 mg/m3 (Worker)
Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)		
Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
		44 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	71 mg/m3 (Consumer)
		330 mg/m3 (Worker)

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Butanone (78-93-3)		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1,161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m3 (Consumer)
Xylene (mix)		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m3 (Consumer)
	DNEL Long term-systemic	14.8 mg/m3 (Worker)
		77 mg/m3 (Worker)
PNECs		
acetone; propan-2-one; propanone (67-64-1)		
PNEC Marine water	1.06 (Undefined)	
PNEC Freshwater sediment	30.4 (Undefined)	
PNEC Soil	29.5 (Undefined)	
PNEC Marine water sediment	3.04 (Undefined)	
Xylene (mix)		
PNEC Freshwater	0.327 (Undefined)	
PNEC Marine water	0.327 (Undefined)	
PNEC Freshwater sediment	12.46 (Undefined)	
PNEC Soil	2.31 (Undefined)	
PNEC Sewage Treatment Plant	6.58 (Undefined)	
PNEC Marine water sediment	12.46 (Undefined)	
Ingredients with biological limit values:		
Butanone (78-93-3)		
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	
Xylene (mix)		
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	

8.2. Exposure controls

Appropriate engineering controls:

Wash hands before breaks and after work. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

Hand protection:

Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)		0.5		

Eye protection:

Protective goggles

Type	Use	Characteristics	Standard
			EN 166

Skin and body protection:

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Standard
	EN 13034

Respiratory protection:

Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: No data available
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55.8 - 56.6 °C
Flash point	: -97 °C
Auto-ignition temperature	: 365 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 8300 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.71 g/cm ³ (20°C)
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.6 vol %
Upper explosive limit (UEL)	: 13 vol %

9.2. Other information

VOC content	: 609.3 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
-----------------------	------------------

LD/LC50 values relevant for classification:

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acetone (67-64-1)		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	7,800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)
Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
Butanone (78-93-3)		
Oral	LD50	>2,193 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rbt)
Xylene (mix)		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)

Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified
Skin corrosion/irritation	:	Not classified
Serious eye damage/irritation	:	Causes serious eye irritation.
Respiratory or skin sensitisation	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified

STOT-single exposure	:	May cause drowsiness or dizziness.
STOT-repeated exposure	:	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	:	May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity	:	Not classified
Chronic aquatic toxicity	:	Harmful to aquatic life with long lasting effects.

Acetone (67-64-1)	
EC50	8,800 mg/l (Daphnia magna) 8,300 mg/l (Fish)
Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)	
NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	10-22 mg/l (Daphnia magna)
EL50 (72h)	4.6-10 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	10-30 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.097 mg/l (Daphnia magna)
LOEC (21 days)	0.203 mg/l (Daphnia magna)
Butanone (78-93-3)	
LC50/96h	2,993 mg/l (Pimephales promelas)
EC50/48h	308 mg/l (Daphnia magna)
Xylene (mix)	
NOEC	1.3 mg/l (Fish)
NOEC (7 day)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Do not dispose of with domestic waste. Prevent entry to sewers and public waters.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
1950	1950	1950	1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Not applicable	Not applicable
Transport document description			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950	UN 1950
14.3. Transport hazard class(es)			
2.1	2.1	Not applicable	Not applicable
		Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 11
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12
Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Air transport

No data available

- Inland waterway transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Class	Share in %
NK	75-<100

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 609.3 g/l

VOC-CH 85,82%

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 1, low hazard to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed

SZW-lijst van mutagene stoffen : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1

High Gloss black - 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains (cobalt bis(2-ethylhexanoate)). May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product