



## 1-151 Uni Thinner Standard

### APPLICATION DATA




: See application data on our products.



**Application viscosity**  
**DINCUP 4mm/20°C**

: Airspray (sec) : -  
: Pressure tank (sec) : -  
: Airless (sec) : -

-



Gravity feed  
Suction feed  
Pressure tank  
Airless  
HVLP / LVLP  
HE


Nozzle diameter (mm)

Spraying pressure (bar)

-  
-  
-  
-  
-  
-  
-  
See Info Manufacturer  
See Info Manufacturer



**Spray coats / Layer thickness**  
**(µm)** : - / -



**Flash-off (min)** : -



**Drying time (min)**    **20°C** : -  
                                  **60°C Obj.** : -



**Potlife (min)**        **20°C** : -

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.

## 1-151 Uni Thinner Standard



### PRODUCT INFO

- Area of application** : Thinners for amongst others Series 400 and Series 500. Do not use in combination with synthetic products, Series 900, Series 3000 HS420.
- Chemical base** : Organic solvents thinners.
- General qualities** : 1-151 Uni Thinner Standard for application at 18°- 25°C.
- Auxiliary materials** : All products except Synthetic products

<b>Physical properties</b>	<b>Specific gravity (kg/l)</b>	: 0.904
	<b>Flash point</b>	: Closed cup: 28°C (82.4°F)
	<b>Vol.% solids</b>	: 0
	<b>Economy</b>	: -
	<b>Gloss</b>	:
	<b>Colour</b>	: Clear.

- Substrates** : See application data on our products:
- Undercoats** : See application data on our products
- Finishing materials** : See application data on our products
- Cleaning the equipment** : -
- Storage life (years)** : min. 2  
(Under normal storage conditions and unopened tins).

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.