



47-65 MS Hardener Slow

APPLICATION DATA



Mixing Ratio


: See 1-104, 1-105, 8-145 and Series 400/700.



Application viscosity DINCUP 4mm/20°C

: Airspray (sec) : -
: Pressure tank (sec) : -
: Airless (sec) : -

(*) Shelf life: Depending on temperatures and humidity.
The tin should be closed immediately after use.



Gravity feed
Suction feed
Pressure tank
Airless
HVLP / LVLP
HR

Nozzle diameter (mm)

-
-
-
-
-
-


Spraying pressure (bar)

-
-
-
-
See Info Manufacturer
See Info Manufacturer



Spray coats / Layer thickness (µm)

: - / -



Flash-off (min)

: -



Drying time (min)

20°C : -
60°C Obj. : -



Potlife (min)

20°C : -

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.

47-65 MS Hardener Slow



PRODUCT INFO

- Area of application** : Car repair and commercial vehicles.
- Chemical base** : Non-yellowing, highly durable isocyanate resin
- General qualities** : The MS Hardeners are divided according to use at different temperatures: See survey Hardeners and Thinners. MS Hardener Slow 47-65, for use at higher temperatures and/or on large objects, 25-35° C.
- Auxiliary materials** : 1-104, 1-105, 8-145, 1-141/1-151/1-161, Series 400, Series 700

Physical properties	Specific gravity (kg/l)	: 1.024
	Flash point	: Closed cup: 36°C (96.8°F)
	Vol.% solids	: 40
	Economy	: -
	Gloss	:
	Colour	: Clear.

- Substrates** : See info 1-104/1-105, 8-145 and Series 400/700.
- Undercoats** : See Info 1-104/1-105, 8-145 and Series 400/700
- Finishing materials** : See info 1-104/1-105, 8-145 and Series 400/700
- Cleaning the equipment** : 1-051 Gun Cleaner
- Storage life (years)** : min. 1 (*)
(Under normal storage conditions and unopened tins).

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.