

# SAFETY DATA SHEET



SP2511 HS Hardener Fast

## Section 1. Identification

**Product name** : SP2511 HS Hardener Fast

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

### Identified uses

Use in coatings - Hardener.

### Supplier

**Manufacturer** : Valspar b.v.  
Zuiveringweg 89  
8243 PE Lelystad  
The Netherlands  
tel: +31 (0)320 292200  
fax: +31 (0)320 292201

valspar

**Emergency telephone number** : Call: +31 (0)320 292200 (during daytime)

**Supplier's details** : DBNZ Coatings Limited  
6 Killarney Lane  
Hamilton 3204  
NEW ZEALAND  
T: +64 7847 0944  
E: info@dbnz.co.nz

**Emergency telephone number (with hours of operation)** : New Zealand Poisons Information Centre: 0800 764766 (24 hrs)  
CALL: +(64)-98010034 (Hours of operation - 24 hours)

**e-mail address of person responsible for this SDS** : msds@de-beer.com

## Section 2. Hazards identification

**HSNO Classification** : 3.1 - FLAMMABLE LIQUIDS - Category C  
6.1 - ACUTE TOXICITY (oral) - Category E  
6.1 - ACUTE TOXICITY (inhalation) - Category D  
6.3 - SKIN IRRITATION - Category B  
6.4 - EYE IRRITATION - Category A (Irritant)  
6.5 - SENSITIZATION - Category A (Respiratory)  
6.7 - CARCINOGENICITY - Category B  
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY - Category B  
6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B  
9.1 - AQUATIC ECOTOXICITY - Category C

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

### GHS label elements

**Signal word** : Danger

## Section 2. Hazards identification

**Hazard statements** : Flammable liquid and vapour.  
 May be harmful if swallowed.  
 Causes mild skin irritation.  
 Causes serious eye irritation.  
 Harmful if inhaled.  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child.  
 May cause damage to organs.  
 Harmful to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye/face protection. Wear appropriate respiratory protection. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Response** : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

**Storage** : Store locked up. Store in a well-ventilated place. Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Symbol** : 

**Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

| Ingredient name                          | % (w/w)  | CAS number |
|--|----------|------------|
| Aliphatic polyisocyanate                 | 25 - 50  | 28182-81-2 |
| 2-methoxy-1-methylethyl acetate          | 25 - 50  | 108-65-6   |
| xylene                                   | 5 - 12.5 | 1330-20-7  |
| Solvent naphtha (petroleum), light arom. | 5 - 12.5 | 64742-95-6 |
| 1,2,4-trimethylbenzene                   | 5 - 12.5 | 95-63-6    |
| n-butyl acetate                          | 1 - 5    | 123-86-4   |
| ethylbenzene                             | 1 - 5    | 100-41-4   |
| mesitylene                               | 1 - 5    | 108-67-8   |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Inhalation** : Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if adverse health effects persist or are severe. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Inhalation** : Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Ingestion** : May be harmful if swallowed.
- Skin contact** : Causes mild skin irritation.
- Eye contact** : Causes serious eye irritation.

#### Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:  
wheezing and breathing difficulties  
asthma  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : Not available.

## Section 4. First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Specific hazards arising from the chemical** : Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides
- Hazchem code** : 3Y
- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Methods and material for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

## Section 6. Accidental release measures

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

- Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                 | Exposure limits  |
|---------------------------------|--|
| Aliphatic polyisocyanate        | <b>NZ HSWA 2015 (New Zealand, 11/2018). Skin sensitiser.</b><br>WES-TWA: 0.02 mg/m <sup>3</sup> , (measured as - NCO) 8 hours.<br>WES-STEL: 0.07 mg/m <sup>3</sup> , (measured as - NCO) 15 minutes.               |
| 2-methoxy-1-methylethyl acetate | <b>EH40/2005 WELs (United Kingdom (UK), 8/2018). Absorbed through skin.</b><br>STEL: 548 mg/m <sup>3</sup> 15 minutes.<br>TWA: 50 ppm 8 hours.<br>TWA: 274 mg/m <sup>3</sup> 8 hours.<br>STEL: 100 ppm 15 minutes. |
| xylene                          | <b>NZ HSWA 2015 (New Zealand, 11/2018). Notes: See Notice of Intended Changes.</b><br>WES-TWA: 217 mg/m <sup>3</sup> , 0 times per shift, 8 hours.<br>WES-TWA: 50 ppm, 0 times per shift, 8 hours.                 |
| 1,2,4-trimethylbenzene          | <b>NZ HSWA 2015 (New Zealand, 11/2018).</b><br>WES-TWA: 25 ppm 8 hours.<br>WES-TWA: 123 mg/m <sup>3</sup> 8 hours.   |
| n-butyl acetate                 | <b>NZ HSWA 2015 (New Zealand, 11/2018).</b><br>WES-TWA: 150 ppm 8 hours.   |

## Section 8. Exposure controls/personal protection

|              |  |
|--------------|--|
| ethylbenzene | WES-TWA: 713 mg/m <sup>3</sup> 8 hours.<br>WES-STEL: 950 mg/m <sup>3</sup> 15 minutes.<br>WES-STEL: 200 ppm 15 minutes.<br><b>NZ HSWA 2015 (New Zealand, 11/2018).</b><br>WES-STEL: 543 mg/m <sup>3</sup> 15 minutes.<br>WES-STEL: 125 ppm 15 minutes.<br>WES-TWA: 434 mg/m <sup>3</sup> 8 hours.<br>WES-TWA: 100 ppm 8 hours. |
| mesitylene   | <b>NZ HSWA 2015 (New Zealand, 11/2018).</b><br>WES-TWA: 25 ppm 8 hours.<br>WES-TWA: 123 mg/m <sup>3</sup> 8 hours.   |

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: full-face mask supplied-air respirator.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 butyl rubber polyvinyl alcohol (PVA) Viton® ≥ 0.7 mm  
4 - 8 hours (breakthrough time): Recommended EN 374 neoprene ≥ 0.7 mm  
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (≥ 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.

## Section 9. Physical and chemical properties

### Appearance

|  |   |
|--|---|
| Physical state                                 | : Liquid.   |
| Colour   | : Colourless.   |
| Odour  | : Not available.  |
| Odour threshold                                | : Not available.  |
| pH   | : Not applicable.   |
| Melting point                                  | : Not available.  |
| Boiling point                                  | : >100°C (>212°F)   |
| Flash point                                    | : Closed cup: 36°C (96.8°F)                                       |
| Evaporation rate                               | : Not available.  |
| Flammability (solid, gas)                      | : Not available.  |
| Lower and upper explosive (flammable) limits   | : Lower: 1.2%<br>Upper: 10.8%                                     |
| Vapour pressure                                | : Not available.  |
| Vapour density                                 | : 4.4 [Air = 1]   |
| Relative density                               | : 1.008   |
| Solubility                                     | : Insoluble in the following materials: cold water and hot water. |
| Solubility in water                            | : Not available.  |
| Partition coefficient: n-octanol/water         | : Not available.  |
| Auto-ignition temperature                      | : Not available.  |
| Decomposition temperature                      | : Not available.  |
| Viscosity                                      | : Kinematic (40°C (104°F)): 0.04 cm <sup>2</sup> /s (4 cSt)       |
| Flow time (ISO 2431)                           | : Not available.  |
| <b>Aerosol product</b>                         |   |
| Type of aerosol                                | : Not applicable.   |
| Heat of combustion                             | : Not available.  |
| Ignition distance                              | : Not applicable.   |
| Enclosed space ignition - Time equivalent      | : Not applicable.   |
| Enclosed space ignition - Deflagration density | : Not applicable.   |
| Flame height                                   | : Not applicable.   |
| Flame duration                                 | : Not applicable.   |

## Section 10. Stability and reactivity

|                                    |   |
|------------------------------------|---|
| Chemical stability                 | : The product is stable.  |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| Conditions to avoid                | : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas. |
| Incompatible materials             | : Reactive or incompatible with the following materials:<br>oxidising materials   |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## Section 11. Toxicological information

### Information on likely routes of exposure

- Inhalation** : Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Ingestion** : May be harmful if swallowed.
- Skin contact** : Causes mild skin irritation.
- Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
wheezing and breathing difficulties  
asthma  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Acute toxicity

| Product/ingredient name                  | Result                          | Species                  | Dose                    | Exposure |
|--|---------------------------------|--------------------------|-------------------------|----------|
| Aliphatic polyisocyanate                 | LC50 Inhalation Dusts and mists | Rat                      | 2.18 mg/l               | 4 hours  |
|  | LD50 Dermal                     | Rabbit - Male,<br>Female | >2000 mg/kg             | -        |
|  | LD50 Dermal                     | Rat - Male,<br>Female    | >2000 mg/kg             | -        |
| 2-methoxy-1-methylethyl acetate          | LD50 Oral                       | Rat                      | >5000 mg/kg             | -        |
|  | LD50 Dermal                     | Rat                      | >5000 mg/kg             | -        |
| xylene                                   | LD50 Oral                       | Rat - Female             | >5000 mg/kg             | -        |
|  | LC50 Inhalation Gas.            | Rat                      | 6350 ppm                | 4 hours  |
|  | LD50 Dermal                     | Rabbit                   | 12126 mg/kg             | -        |
| Solvent naphtha (petroleum), light arom. | LD50 Oral                       | Rat                      | 3523 to 4000 mg/kg      | -        |
|  | LC50 Inhalation Vapour          | Rat                      | >6193 mg/m <sup>3</sup> | 4 hours  |
|  | LD50 Dermal                     | Rabbit                   | >3160 mg/kg             | -        |
| 1,2,4-trimethylbenzene                   | LD50 Oral                       | Rat                      | 3592 mg/kg              | -        |
|  | LD50 Oral                       | Rat                      | >5000 mg/kg             | -        |
|  | LC50 Inhalation Vapour          | Rat                      | >21.1 mg/l              | 4 hours  |
| n-butyl acetate                          | LD50 Dermal                     | Rabbit                   | >14112 mg/kg            | -        |
|  | LD50 Oral                       | Rat                      | 10760 mg/kg             | -        |
|  | LC50 Inhalation Vapour          | Rat                      | 6350 ppm                | 4 hours  |
| ethylbenzene                             | LD50 Dermal                     | Rabbit                   | 12126 mg/kg             | -        |
|  | LD50 Oral                       | Rat                      | 3523 to 4000 mg/kg      | -        |
|  | LD50 Oral                       | Rat                      | 3523 to 4000 mg/kg      | -        |

#### Irritation/Corrosion



## Section 11. Toxicological information

| Product/ingredient name            | Result                   | Species | Score | Exposure                | Observation |
|------------------------------------|--------------------------|---------|-------|-------------------------|-------------|
| Aliphatic polyisocyanate<br>xylene | Skin - Mild irritant     | Rabbit  | -     | 4 hours                 | -           |
|                                    | Eyes - Mild irritant     | Rabbit  | -     | -                       | -           |
|                                    | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters  | -           |
| ethylbenzene                       | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams | -           |
|                                    | Skin - Moderate irritant | Rabbit  | -     | 100 Percent             | -           |
|                                    | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams           | -           |
|                                    | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams   | -           |
| mesitylene                         | Eyes - Severe irritant   | Rabbit  | -     | 500 milligrams          | -           |
|                                    | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15 milligrams  | -           |
| mesitylene                         | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams | -           |
|                                    | Skin - Moderate irritant | Rabbit  | -     | 24 hours 20 milligrams  | -           |

### Sensitisation

| Product/ingredient name  | Route of exposure | Species    | Result      |
|--------------------------|-------------------|------------|-------------|
| Aliphatic polyisocyanate | skin              | Mouse      | Sensitising |
|                          | skin              | Guinea pig | Sensitising |

### Potential chronic health effects

- General** : No known significant effects or critical hazards.
- Inhalation** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Eye contact** : No known significant effects or critical hazards.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

### Chronic toxicity

| Product/ingredient name  | Result  | Species               | Dose                  | Exposure                 |
|--------------------------|---|-----------------------|-----------------------|--------------------------|
| Aliphatic polyisocyanate | Sub-chronic NOAEL<br>Inhalation Dusts and mists | Rat - Male,<br>Female | 3.3 mg/m <sup>3</sup> | 90 days; 6 hours per day |

### Carcinogenicity

Not available.

### Mutagenicity

| Product/ingredient name  | Test  | Experiment   | Result   |
|--------------------------|---|--|----------|
| Aliphatic polyisocyanate | OECD 471 Bacterial Reverse Mutation Test            | Experiment: In vitro<br>Subject: Bacteria<br>Metabolic activation: +/-         | Negative |
|                          | OECD 476 In vitro Mammalian Cell Gene Mutation Test | Experiment: In vitro<br>Subject: Mammalian-Animal<br>Metabolic activation: +/- | Negative |

### Teratogenicity

## Section 11. Toxicological information

Not available.

### Reproductive toxicity

Not available.

### Specific target organ toxicity

| Name                   | Category   | Route of exposure  | Target organs                    |
|------------------------|------------|--------------------|----------------------------------|
| xylene                 | Category B | Oral<br>Inhalation | Not determined<br>Not determined |
| 1,2,4-trimethylbenzene | Category B | Inhalation         | Not determined                   |
| ethylbenzene           | Category B | Inhalation         | Not determined                   |

### Aspiration hazard

| Name                                     |
|--|
| Solvent naphtha (petroleum), light arom. |

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route                        | ATE value      |
|------------------------------|----------------|
| Oral                         | 4520.43 mg/kg  |
| Dermal                       | 12387.53 mg/kg |
| Inhalation (vapours)         | 138.51 mg/l    |
| Inhalation (dusts and mists) | 4.49 mg/l      |

## Section 12. Ecological information

**Ecotoxicity** : This material is harmful to aquatic life with long lasting effects.

### Aquatic and terrestrial toxicity

| Product/ingredient name                  | Result                  | Species                                 | Exposure |
|--|-------------------------|---|----------|
| Aliphatic polyisocyanate                 | Acute EC50 >1000 mg/l   | Algae - Scenedesmus subspicatus         | 72 hours |
| 2-methoxy-1-methylethyl acetate          | Acute EC50 >100 mg/l    | Daphnia - Daphnia magna                 | 48 hours |
|  | Acute LC50 >100 mg/l    | Fish - Danio rerio                      | 96 hours |
|  | Acute EC50 >1000 mg/l   | Algae - Pseudokirchnerella subcapitata  | 96 hours |
|  | Acute EC50 408 mg/l     | Daphnia - Daphnia magna                 | 48 hours |
| xylene                                   | Acute LC50 134 mg/l     | Fish - Oncorhynchus mykiss              | 96 hours |
|  | Acute EC50 1 to 10 mg/l | Algae                                   | 72 hours |
|  | Acute EC50 1 to 10 mg/l | Daphnia - Daphnia magna                 | 48 hours |
|  | Acute LC50 1 to 10 mg/l | Fish                                    | 96 hours |
| Solvent naphtha (petroleum), light arom. | Acute EC50 2.9 mg/l     | Algae - Pseudokirchneriella subcapitata | 72 hours |
|  | Acute EC50 3.2 mg/l     | Daphnia - Daphnia magna                 | 48 hours |
|  | Acute LC50 9.2 mg/l     | Fish - Oncorhynchus mykiss              | 96 hours |
|  | Acute NOEC >1 mg/l      | Algae - Pseudokirchneriella subcapitata | 72 hours |
| 1,2,4-trimethylbenzene n-butyl acetate   | Acute EC50 1 to 10 mg/l | Fish                                    | 96 hours |
|  | Acute EC50 397 mg/l     | Algae - Selenastrum capricornutum       | 72 hours |
|  | Acute EC50 44 mg/l      | Daphnia - Daphnia magna                 | 48 hours |
|  | Acute LC50 32 mg/l      | Crustaceans - Artemia salina            | 48 hours |
| ethylbenzene                             | Acute LC50 18 mg/l      | Fish - Pimephales promelas              | 96 hours |
|  | Acute NOEC 200 mg/l     | Algae                                   | 72 hours |
|  | Acute LC50 >10 mg/l     | Fish - Pimephales promelas              | 96 hours |

### Persistence/degradability

## Section 12. Ecological information

| Product/ingredient name                  | Test  | Result                      | Dose | Inoculum    |
|--|---|-----------------------------|------|-------------|
| Aliphatic polyisocyanate                 | EU 67/548/EEC ANNEX V, C.4.E.   | 1 % - Not readily - 28 days | -    | -           |
| 2-methoxy-1-methylethyl acetate          | OECD 302B<br>Inherent Biodegradability:<br>Zahn-Wellens/<br>EMPA Test       | 100 % - 28 days             | -    | -           |
| Solvent naphtha (petroleum), light arom. | OECD 301F<br>Ready Biodegradability -<br>Manometric<br>Respirometry<br>Test | 83 % - 28 days              | -    | -           |
| n-butyl acetate                          | -   | 78 % - Readily - 28 days    | -    | Fresh water |
|  | OECD 301D<br>Ready Biodegradability -<br>Closed Bottle<br>Test              | >80 % - 5 days              | -    | -           |

| Product/ingredient name                  | Aquatic half-life          | Photolysis | Biodegradability |
|--|----------------------------|------------|------------------|
| Aliphatic polyisocyanate                 | Fresh water 7.7 days, 23°C | -          | Not readily      |
| 2-methoxy-1-methylethyl acetate          | -                          | -          | Readily          |
| Solvent naphtha (petroleum), light arom. | -                          | -          | Readily          |
| n-butyl acetate                          | -                          | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name                  | LogP <sub>ow</sub> | BCF         | Potential |
|--|--------------------|-------------|-----------|
| Aliphatic polyisocyanate                 | 5.54               | 367.7       | low       |
| 2-methoxy-1-methylethyl acetate          | 1.2                | -           | low       |
| xylene                                   | 3.12               | 8.1 to 25.9 | low       |
| Solvent naphtha (petroleum), light arom. | -                  | 10 to 2500  | high      |
| 1,2,4-trimethylbenzene                   | 3.63               | 243         | low       |
| n-butyl acetate                          | 2.3                | -           | low       |
| ethylbenzene                             | 3.6                | -           | low       |
| mesitylene                               | 3.42               | 161         | low       |

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.







## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the

## Section 13. Disposal considerations

container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

| Regulatory information | UN number | Proper shipping name   | Classes | PG* | Label   |
|------------------------|-----------|------------------------|---------|-----|---|
| New Zealand Class      | UN1263    | PAINT RELATED MATERIAL | 3       | III |    |
| ADG Class              | UN1263    | PAINT RELATED MATERIAL | 3       | III |    |
| UN Class               | UN1263    | PAINT RELATED MATERIAL | 3       | III |    |
| ADR/RID Class          | UN1263    | PAINT RELATED MATERIAL | 3       | III |    |
| IATA Class             | UN1263    | Paint related material | 3       | III |  |
| IMDG Class             | UN1263    | PAINT RELATED MATERIAL | 3       | III |  |

### Additional information

- New Zealand Class** : **Hazchem code** 3Y
- ADG Class** : **Hazchem code** •3Y  
**Special provisions** 163, 223
- UN Class** : **Special provisions** 163, 223
- ADR/RID Class** : **Hazard identification number** 30  
**Limited quantity** 5 L  
**Special provisions** 163 640E 650  
**Tunnel code** (D/E)
- IATA Class** : **Quantity limitation** Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344.  
**Special provisions** A3, A72
- IMDG Class** : **Emergency schedules** F-E, \_S-E\_  
**Special provisions** 163, 223, 955

PG\* : Packing group

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

|                             |   |
|-----------------------------|---|
| <b>HSNO Approval Number</b> | : HSR002669   |
| <b>HSNO Group Standard</b>  | : Surface Coatings and Colourants   |
| <b>HSNO Classification</b>  | : 3.1 - FLAMMABLE LIQUIDS - Category C<br>6.1 - ACUTE TOXICITY (oral) - Category E<br>6.1 - ACUTE TOXICITY (inhalation) - Category D<br>6.3 - SKIN IRRITATION - Category B<br>6.4 - EYE IRRITATION - Category A (Irritant)<br>6.5 - SENSITIZATION - Category A (Respiratory)<br>6.7 - CARCINOGENICITY - Category B<br>6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY - Category B<br>6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B<br>9.1 - AQUATIC ECOTOXICITY - Category C |

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

|                          |   |
|--------------------------|---|
| <b>Australia</b>         | : All components are listed or exempted.  |
| <b>Canada</b>            | : All components are listed or exempted.  |
| <b>China</b>             | : All components are listed or exempted.  |
| <b>Europe</b>            | : All components are listed or exempted.  |
| <b>Japan</b>             | : <b>Japan inventory (ENCS)</b> : All components are listed or exempted.<br><b>Japan inventory (ISHL)</b> : Not determined. |
| <b>Malaysia</b>          | : Not determined  |
| <b>New Zealand</b>       | : All components are listed or exempted.  |
| <b>Philippines</b>       | : All components are listed or exempted.  |
| <b>Republic of Korea</b> | : All components are listed or exempted.  |
| <b>Taiwan</b>            | : All components are listed or exempted.  |
| <b>Thailand</b>          | : Not determined.   |
| <b>Turkey</b>            | : Not determined.   |
| <b>United States</b>     | : Not determined.   |
| <b>Viet Nam</b>          | : Not determined.   |

## Section 16. Other information

### History

|                                       |              |
|---------------------------------------|--------------|
| <b>Date of printing</b>               | : 12/18/2020 |
| <b>Date of issue/Date of revision</b> | : 12/18/2020 |
| <b>Date of previous issue</b>         | : 12/18/2020 |
| <b>Version</b>                        | : 1          |

## Section 16. Other information

**Key to abbreviations** :

- ADG = Australian Dangerous Goods
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- UN = United Nations

**References** : Not available.

✔ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.